

GENERAL DATA

MODEL:	MTU2000SP
ESP:	2200 kVA
PRP:	2000 kVA
VOLTAGE:	400 V
FREQUENCY:	50 Hz
CURRENT:	2601 A
FUEL:	Diesel
WEIGHT:	20000 KG
DIMENSIONS:	12000 x 2400 x 2600 mm



ENGINE

BRAND:	MTU
TYPE:	16V4000G23
EMISSION:	non
POWER:	1738 kW
RPM:	1500
SPEED REGULATION:	Electronic
NO OF CYLINDERS:	16
DISPLACEMENT:	76,2 L
OIL CAPACITY:	300 L

ALTERNATOR

BRAND:	Leroy Somer
TYPE:	LSA 51.2 M60
IP PROTECTION:	IP23
INSULATION CLASS:	H

GENERAL EQUIPMENT

- COMAP IL3 AMF 25 controller
- 4 pole circuit breaker Schneider
- Emergency stop
- Silenced canopy made with Al.Zn
- Standard Color: Orange
- Fuel filling cap: outside of the canopy
- Fuel level measurement
- Forklift brackets
- Connections behind doors with keys
- Engine heater
- Battery charger

FUEL

Fuel tank:	2000 L
Autonomy 100% load:	6,5 H
Fuel consumption:	
50% load:	215 L/H
75% load:	307 L/H
100% load:	403 L/H

Dutry Power Roeselare
Brugsesteenweg 512
8800 Roeselare
+32(0)51 20 00 88

Dutry Power SPL
Bergensesteenweg 838
1600 Sint Pieters Leeuw
+32(0)2 377 75 23

Dutry Power Lux
Rue de la Croissance 6
6900 Aye
+32 (0)84 31 69 27