

GENERAL DATA

MODEL:	MTU800SP
ESP:	880 kVA
PRP:	800 kVA
VOLTAGE:	400 V
FREQUENCY:	50 Hz
CURRENT:	1156 A
FUEL:	Diesel
WEIGHT:	10000 KG
DIMENSIONS:	6640 x 2300 x 2600 mm



ENGINE

BRAND:	MTU
TYPE:	12V000G26F
EMISSION:	non
POWER:	709 kW
RPM:	1500
SPEED REGULATION:	Electronic
NO OF CYLINDERS:	12
DISPLACEMENT:	26,8 L
OIL CAPACITY:	80 L

ALTERNATOR

BRAND:	Leroy Somer
TYPE:	TAL 049C
IP PROTECTION:	IP23
INSULATION CLASS:	H

GENERAL EQUIPMENT

- COMAP IL3 AMF 25 controller
- 4 pole circuit breaker Schneider
- Emergency stop
- Silenced canopy made with Al.Zn
- Standard Color: Orange
- Fuel filling cap: outside of the canopy
- Fuel level measurement
- Forklift brackets
- Connections behind doors with keys
- Engine heater
- Battery charger

FUEL

Fuel tank:	1000 L
Autonomy 100% load:	8,1 H
Fuel consumption:	
50% load:	87,1 L/H
75% load:	123,6 L/H
100% load:	162,3 L/H

Dutry Power Roeselare
Brugsesteenweg 512
8800 Roeselare
+32(0)51 20 00 88

Dutry Power SPL
Bergensesteenweg 838
1600 Sint Pieters Leeuw
+32(0)2 377 75 23

Dutry Power Lux
Rue de la Croissance 6
6900 Aye
+32 (0)84 31 69 27