

GENERAL DATA

MODEL:	FDG250WA
ESP:	275 kVA
PRP:	250 kVA
VOLTAGE:	400 V
FREQUENCY:	50 Hz
CURRENT:	361 A
FUEL:	Diesel
DIMENSIONS:	3940 x 1650 x 2080 mm



ENGINE

BRAND:	Baudouin
TYPE:	6M16G275/5
EMISSION:	non emission
POWER:	227 kW
RPM:	1500
SPEED REGULATION:	Electronic
NO OF CYLINDERS:	6
DISPLACEMENT:	9,7 L
OIL CAPACITY:	22 L

ALTERNATOR

BRAND:	Leroy Somer
TYPE:	TAL 046D
IP PROTECTION:	IP23
INSULATION CLASS:	H

GENERAL EQUIPMENT

COMAP AMF 25 controller
 Engine preheating with thermostat
 Battery charger
 4 pole circuit breaker Schneider
 Emergency stop
 Silenced canopy made with Al.Zn
 Standard Color: RAL 7024
 Fuel filling cap: outside of the canopy
 Fuel level measurement
 Forklift brackets

FUEL

Fuel tank:	990 L
Autonomy 100% load:	16 H
Fuel consumption:	
50% load:	27,5 L/H
75% load:	40,7 L/H
100% load:	54,8 L/H

Dutry Power Roeselare
Brugsesteenweg 512
8800 Roeselare
+32(0)51 20 00 88

Dutry Power SPL
Bergensesteenweg 838
1600 Sint Pieters Leeuw
+32(0)2 377 75 23

Dutry Power Lux
Rue de la Croissance 6
6900 Aye
+32 (0)84 31 69 27