



**LIGHT & POWER BY DUTRY POWER**

### GENERAL DATA

<b>MODEL:</b>	FDG40WA
<b>ESP:</b>	44 kVA
<b>PRP:</b>	40 kVA
<b>VOLTAGE:</b>	400 V
<b>FREQUENCY:</b>	50 Hz
<b>CURRENT:</b>	57 A
<b>FUEL:</b>	Diesel
<b>DIMENSIONS:</b>	2000 x 1100 x 1490 mm



### ENGINE

<b>BRAND:</b>	Baudouin
<b>TYPE:</b>	4M06G44/5
<b>EMISSION:</b>	non emission
<b>POWER:</b>	35 kW
<b>RPM:</b>	1500
<b>SPEED REGULATION:</b>	Electronic
<b>NO OF CYLINDERS:</b>	4
<b>DISPLACEMENT:</b>	2,3 L
<b>OIL CAPACITY:</b>	9,5 L

### ALTERNATOR

<b>BRAND:</b>	Leroy Somer
<b>TYPE:</b>	TAL 042E
<b>IP PROTECTION:</b>	IP23
<b>INSULATION CLASS:</b>	H

### GENERAL EQUIPMENT

COMAP IL3 AMF 25 controller  
Engine preheating with thermostat  
Battery charger  
4 pole circuit breaker Schneider  
Emergency stop  
Silenced canopy made with Al.Zn  
Standard Color: RAL 7024  
Fuel filling cap: outside of the canopy  
Fuel level measurement  
Forklift brackets

### FUEL

Fuel tank:	210 L
Autonomy 100% load:	21 H
Fuel consumption:	
50% load:	4,7 L/H
75% load:	7 L/H
100% load:	9,5 L/H

**Dutry Power Roeselare**  
Brugsesteenweg 512  
8800 Roeselare  
+32(0)51 20 00 88

**Dutry Power SPL**  
Bergensesteenweg 838  
1600 Sint Pieters Leeuw  
+32(0)2 377 75 23

**Dutry Power Lux**  
Rue de la Croissance 6  
6900 Aye  
+32 (0)84 31 69 27