

GENERAL DATA

MODEL:	FDG200VA
ESP:	220 kVA
PRP:	200 kVA
VOLTAGE:	400 V
FREQUENCY:	50 Hz
CURRENT:	289 A
FUEL:	Diesel
WEIGHT:	2600 KG
DIMENSIONS:	3650 x 1512 x 2226 mm



ENGINE

BRAND:	VOLVO PENTA
TYPE:	TAD733GE
EMISSION:	Stage II
POWER:	176 kW
RPM:	1500
SPEED REGULATION:	Electronic
NO OF CYLINDERS:	6
DISPLACEMENT:	7,2L
OIL CAPACITY:	34L

ALTERNATOR

BRAND:	Leroy Somer
TYPE:	TAL 046B
IP PROTECTION:	IP23
INSULATION CLASS:	H

GENERAL EQUIPMENT

COMAP IL3 AMF 25 controller
 Engine preheating with thermostat
 Battery charger
 4 pole circuit breaker Schneider
 Emergency stop
 Silenced canopy made with Al.Zn
 Standard Color: RAL 7032
 Fuel filling cap: outside of the canopy
 Fuel level measurement
 Forklift brackets

FUEL

Fuel tank:	410 L
Autonomy 100% load:	8,8 H
Fuel consumption:	
50% load:	24,3 L/H
75% load:	35,1 L/H
100% load:	46,6 L/H
110% load:	51,8 L/H

Dutry Power Roeselare
 Brugsesteenweg 512
 8800 Roeselare
 +32(0)51 20 00 88

Dutry Power SPL
 Bergensesteenweg 838
 1600 Sint Pieters Leeuw
 +32(0)2 377 75 23

Dutry Power Lux
 Rue de la Croissance 6
 6900 Aye
 +32 (0)84 31 69 27