

### GENERAL DATA

<b>MODEL:</b>	FH6000
<b>PRP 400 V:</b>	5 kVA
<b>CURRENT :</b>	7,2A
<b>PRP 230V :</b>	3 KVA
<b>CURRENT :</b>	11,7A
<b>VOLTAGE 3F:</b>	400 V
<b>VOLTAGE 1F :</b>	230V
<b>FREQUENCY:</b>	50 Hz
<b>FUEL:</b>	Petrol
<b>WEIGHT:</b>	68 KG
<b>DIMENSIONS:</b>	790 x 580 x 505 mm



### ENGINE

<b>BRAND:</b>	HONDA
<b>TYPE:</b>	GX270
<b>CAPACITY :</b>	270 cm <sup>3</sup>
<b>COOLING :</b>	AIR
<b>CYLINDER :</b>	1
<b>STROKE :</b>	4
<b>OIL :</b>	1,1L
<b>STARTING SYSTEM :</b>	Manuel
<b>FUEL :</b>	Petrol
<b>FUEL TANK :</b>	5,3L
<b>CONSUMPTION :</b>	2,2L/H

### STANDARD EQUIPMENT

**1 socket 230V 16A**  
**1 socket 400V 16A**  
**Overload protection**  
**Oil lever sensor**