



**LIGHT & POWER BY DUTRY POWER**

## GENERAL DATA

<b>MODEL:</b>	IKRN-022
<b>ESP:</b>	20 kVA
<b>PRP:</b>	19 kVA
<b>VOLTAGE:</b>	400 V
<b>FREQUENCY:</b>	50 Hz
<b>CURRENT:</b>	30 A
<b>FUEL:</b>	Diesel
<b>WEIGHT:</b>	1020 KG
<b>DIMENSIONS:</b>	2055 x 1020 x 1535 mm



## ENGINE

<b>BRAND:</b>	Kohler
<b>TYPE:</b>	KDI1903M-SV
<b>EMISSION:</b>	Stage V
<b>POWER:</b>	17,3 kW
<b>RPM:</b>	1500
<b>SPEED REGULATION:</b>	Mechanisch
<b>NO OF CYLINDERS:</b>	3
<b>DISPLACEMENT:</b>	1,86 L
<b>OIL CAPACITY:</b>	8,9 L

## ALTERNATOR

<b>BRAND:</b>	Mecc Alte
<b>TYPE:</b>	ECP 28-M/4
<b>IP PROTECTION:</b>	IP23
<b>INSULATION CLASS:</b>	H

## GENERAL EQUIPMENT

COMAP IL3 AMF 25 controller  
4 pole circuit breaker ABB  
Emergency stop  
Silenced canopy made with Al.Zn  
Standard Color: WHITE  
Fuel filling cap: inside of the canopy  
Fuel level measurement  
Forklift brackets  
Optional big socket panel

## FUEL

Fuel tank:	180 L
Autonomy 100% load:	37,5 H
Fuel consumption:	
50% load:	2,7 L/H
75% load:	4 L/H
100% load:	5,1 L/H

**Dutry Power Roeselare**  
Brugsesteenweg 512  
8800 Roeselare  
+32(0)51 20 00 88

**Dutry Power SPL**  
Bergensesteenweg 838  
1600 Sint Pieters Leeuw  
+32(0)2 377 75 23

**Dutry Power Lux**  
Rue de la Croissance 6  
6900 Aye  
+32 (0)84 31 69 27