



DESCRIPTIVE

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

J130K

Engine ref.	6068TF220
Alternator ref.	LSA 44.3 M6
Performance class	G2

GENERAL CHARACTERISTICS

Frequency (Hz)	50
Voltage (V)	400/230
Standard Control Panel	NEXYS
Optional control panel	TELYS

POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
220 TRI	106	132	96	120	346
220/127	106	132	96	120	346
415/240	106	132	96	120	184
400/230	106	132	96	120	191
380/220	106	132	96	120	201
200/115	106	132	96	120	381
240 TRI	106	132	96	120	318
230 TRI	106	132	96	120	331

DIMENSIONS COMPACT VERSION

Length (mm)	2370
Width (mm)	1114
Height (mm)	1480
Dry weight (kg)	1498
Tank capacity (L)	340

DIMENSIONS SOUNDPROOFED VERSION

Commercial reference of the enclosure	M226
Length (mm)	3508
Width (mm)	1200
Height (mm)	1830
Dry weight (kg)	2088
Tank capacity (L)	340
Acoustic pressure level @1m in dB(A)	75
Sound power level guaranteed (Lwa)	93



J130K

ENGINE CHARACTERISTICS

GENERAL ENGINE DATA

Engine model	JOHN DEERE
Engine ref.	6068TF220
Air inlet	Turbo
Cylinders arrangement	L
Number of cylinders	6
Displacement (C.I.)	6.72
Air coolant	N/A
Bore (mm) x Stroke (mm)	106 x 127
Compression ratio	17 : 1
Speed (RPM)	1500
Pistons speed (m/s)	6.35
Maximum stand-by power at rated RPM (kW)	120
Frequency regulation (%)	+/- 2.5%
BMEP (bar)	12.97
Governor type	Mechanical

COOLING SYSTEM

Radiator & Engine capacity (L)	27.30
Max water temperature (°C)	105
Outlet water temperature (°C)	93
Fan power (kW)	3
Fan air flow w/o restriction (m ³ /s)	4.40
Available restriction on air flow (mm EC)	20
Type of coolant	Glycol-Ethylene
Thermostat (°C)	82-94

EMISSIONS

Emission PM (mg/Nm ³)	60
Emission CO (mg/Nm ³)	140
Emission HCNO _x (g/kWh)	N/A
Emission HC (mg/Nm ³)	42

EXHAUST

Exhaust gas temperature (°C)	561
Exhaust gas flow (L/s)	290
Max. exhaust back pressure (mm EC)	750

FUEL

Consumption @ 110% load (L/h)	29
Consumption @ 100% load (L/h)	26
Consumption @ 75% load (L/h)	18.50
Consumption @ 50% load (L/h)	13.50
Maximum fuel pump flow (L/h)	108

OIL

Oil capacity (L)	21.50
Min. oil pressure (bar)	1
Max. oil pressure (bar)	5
Oil consumption 100% load (L/h)	0.0290
Carter oil capacity (L)	20.60

HEAT BALANCE

Heat rejection to exhaust (kW)	94
Radiated heat to ambient (kW)	14
Heat rejection to coolant (kW)	65

AIR INTAKE

Max. intake restriction (mm EC)	625
Intake air flow (L/s)	135



J130K

ALTERNATOR CHARACTERISTICS

GENERAL DATA

Alternator brand	LERROY SOMER
Alternator ref.	LSA 44.3 M6
Number of phase	3
Power factor (Cos Phi)	0.80
Altitude (m)	0 to 1000
Overspeed (rpm)	2250
Number of pole	4
Excitation system	SHUNT
Insulation class	H
T° class, continuous 40°C	H / 125°K
AVR Type	R250
Total Harmonic Distortion in no-load DHT (%)	<2
Wave form : NEMA=TIF	<50
Wave form : CEI=FHT	N/A
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (%)	+/- 0.5%
Recovery time (Delta U = 20% transient) (ms)	500

OTHER DATA

Continuous Nominal Rating 40°C (kVA)	125
Standby Rating 27°C (kVA)	138
Efficiencies 4/4 load (%)	92.40
Air flow (m3/s)	0.25
Short circuit ratio (Kcc)	0.44
Direct axis synchro reactance unsaturated (Xd) (%)	329
Quadra axis synchro reactance unsaturated (Xq) (%)	197
Open circuit time constant (T"do) (ms)	2154
Direct axis transient reactance saturated (X"d) (%)	15.20
Short circuit transient time constant (T"d) (ms)	100
Direct axis subtransient reactance saturated (X""d) (%)	9.10
Subtransient time constant (T""d) (ms)	10
Quadra axis subtransient reactance saturated (X""q) (%)	18.60
Zero sequence reactance unsaturated (Xo) (%)	0.04
Negative sequence reactance saturated (X2) (%)	13.89
Armature time constant (Ta) (ms)	15
No load excitation current (io) (A)	0.65
Full load excitation current (ic) (A)	2.39
Full load excitation voltage (uc) (V)	29.80
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	289.10
Transient dip (4/4 load) - PF : 0,8 AR (%)	13.80
No load losses (W)	2320
Heat rejection (W)	10174

DIMENSIONS

CONTAINMENT

Commercial reference of the enclosure	M226 DW
Length (mm)	3560
Width (mm)	1200
Height (mm)	2182
Dry weight (kg)	2488
Tank capacity (L)	868
Acoustic pressure level @1m in dB(A)	74
Sound power level guaranteed (Lwa)	93

CONTAINMENT 48H

Commercial reference of the enclosure	M226 DW48
Length (mm)	3560
Width (mm)	1200
Height (mm)	2358
%PdnetE_3%	2656
Tank capacity (L)	1630
Acoustic pressure level @1m in dB(A)	74
Sound power level guaranteed (Lwa)	93

NEXYS, comprehensive and simple



The NEXYS is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly NEXYS offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

Standard electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, engine speed, battery voltage, fuel level.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed (sup. to 60 Kva), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

TELYS, ergonomic and user-friendly



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.

